Safety data sheet Nylon

Ultimaker

1. Identification of the substance / preparation and of the company

1.1 Trade name Nylon

1.2 Use of the product 3D printer filament

1.3 Supplier Ultimaker B.V.

Watermolenweg 2 4191 PN, Geldermalsen

The Netherlands

Emergency phone number In case of toxicological emergency, contact your doctor

2. Hazards identification according to regulation (EC) No 1272/2008 and GHS

2.1 Classification of the substance or mixture No risk exists to the health of users if the product is

handled and processed properly

2.2 Label elements Not applicable2.3 Other hazards Not known

3. Composition / information on ingredients

3.1 Composition Polyamide (grade based on PA6/PA66)

3.2 Mixture Not applicable

4. First-aid measures

4.1 Description of first-aid measures

General advice If you feel unwell, seek medical advice (show the label where

possible). Never give anything by mouth to an unconscious

person

Inhalation In case of inhalation of gases released from molten filament,

move person into fresh air

Skin contact Wash with soap and water. Seek medical attention if symptoms

occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water – do not try to peel it off. Seek medical attention, if necessary, for

material removal and treatment of the burns

Eye contact Any material that contacts the eye should be washed out

immediately with water. If easy to do, remove contact lenses. Seek medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at

least 15 minutes. Seek medical attention immediately

Ingestion Not probable. Seek medical advice in case ingestion occurs

Note to physician Treat symptomatically

4.2 Most important symptoms and effects, both acute and delayed

Burns should be treated as thermal burns. The material will come off as healing occurs; therefore immediate removal from skin is not necessary

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. Firefighting measures

5.1 General advice Material can accumulate static charges, which may cause an

electrical spark (ignition source). Use proper bonding and/or

grounding procedures

5.2 Extinguishing media Foam, carbon dioxide (CO₂), water, or dry chemical

Unsuitable extinguishing media: not known

5.3 Special hazards arising from the

substance or mixture

Burning produces unpleasant and toxic fumes: carbon oxides

 (CO_x)

5.4 Advice for firefighters Use self-contained breathing apparatus and full protective

clothing

6. Accidental release measures

6.1 Personal precautions, protective equipment, and emergency procedures Avoid breathing gases released from molten filament. Ensure

adequate ventilation, especially in confined areas

6.2 Environmental precautions

6.3 Methods and materials for containment

and cleaning up

Allow to solidify molten material. Dispose of waste and residue

according to local regulations

No data available

6.4 Reference to other sections

7. Handling and storage

7.1 Precautions for safe handling Avoid contact with molten material

7.2 Conditions for safe storage, including any

incompatibilities

Product should be stored in a dry and cool place at temperatures between -20 to +30 °C. Avoid direct sunlight. Minimize moisture uptake by leaving it in a sealed package with the supplied

desiccant

7.3 Specific end use(s) Filament for 3D printing

8. Exposure controls / personal protection

8.1 Control parameters None

No data available **DNEL PNEC** No data available

8.2 Exposure controls

Eye protection Use safety glasses for prolonged staring at printing

Skin and body protection Good practice suggests to minimize skin contact. When material

is heated, wear gloves to protect against thermal burns

Respiratory protection If engineering controls do not maintain airborne concentrations

below recommended exposure limits (when applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be used. Respirator type: air-purifying respirator with an appropriate government-approved (where applicable) air-purifying filter, cartridge, or canister. Contact a health and safety professional or

manufacturer for specific information

Hand protection Follow good industrial hygiene practices
Hygiene measures Follow good industrial hygiene practices

Engineering measures Good general ventilation (typically 10 air char

Good general ventilation (typically 10 air changes per hour) is recommended. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls that maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Filament

Color Transparent and black

Odor Slight
Flash point > 400 °C

Ignition temperature -

Thermal decomposition > 300 °C

Auto-ignition temperature > 430 °C

Melting point / range 185 - 195 °C

Density 1.14 g/cm³

Water solubility Insoluble

Solubility in other solvents Sulfuric acid, 96%

9.2 Other information -

10. Stability

Stable under recommended storage conditions

10.1 Reactivity No data available

10.2 Chemical stability Good chemical stability

10.3 Possibility of hazardous reactions No decomposition or hazardous reactions if stored and applied

as directed

10.4 Conditions to avoid Print temperatures above 280 °C (at standard printing speeds)

10.5 Incompatible materials -

10.6 Hazardous decomposition products See 5.2

11. Toxicological information

11.1 Information on toxicological effects

Principal routes of exposure Eye contact, skin contact, inhalation, ingestion

Acute toxicity There were no target organ effects noted following ingestion or

dermal exposure in animal studies

Skin corrosion / irritation May cause eye / skin irritation. Product dust may be irritating to

the eyes, skin, and respiratory system

Serious eye damage / eye irritation No data available Respiratory or skin sensitization No data available Reproductive toxicity No data available Carcinogenicity No data available

12. Ecological information

To date, proper use of the filament has not been associated with 12.1 Toxicity

No data available

any detrimental effect on health

12.2 Persistence and degradability Non-degradable Bio accumulate 12.3 Bioaccumulative potential 12.4 Mobility in soil No data available 12.5 Results of PBT and vPvB assessment No data available 12.6 Other adverse effects

13. Disposal considerations

13.1 Waste treatment methods In accordance with local and national regulations

14. Transport information

ADR Not regulated RID Not regulated IATA Not regulated **IMDG** Not regulated

Special precautions for user

15. Regulatory information

Not meant to be all-inclusive - selected regulations represented

15.1 Safety, health, and environmental regulations / legislation specific for the substance or mixture

US Regulations:

Sara 313 title III -

TSCA Inventory List -

OSHA hazard category -

CERCLA -

WHMIS -

State right-to-know requirements

Other Inventories:

Canada DSL Inventory List

REACH / EU EINIECS Components are in compliance with REACH

EU/722/2012 -

NEHAPS -

Japan (ECL/MITI) -

Australia (AICS) -

Korean toxic substances control act (ECL) -

Philippines inventory (PICCS) -

Chinese chemical inventory (IECSC)

15.2 Chemical Safety Assessment No data available

16. Other information

The information provided in this Safety Data Sheet (SDS) is based on current knowledge and experience. This information is provided without warranty. This information should help to make an independent determination of the methods to ensure proper and safe use and disposal of the filament

Version Version 4.002

Date January 14, 2019